

Mitsubishi OBD-Prog v 4.7

Mitsubishi OBD-Prog v4.7 – is a standalone device for electronic key registration on Mitsubishi passenger vehicles. The device also supports Peugeot 4007 and Citroen C-croser vehicles with similar key authorization systems.



Operation sequence (step-by-step instruction)

1. Make sure the vehicle's battery is fully charged.
2. Prepare "Mitsubishi OBD-Prog" by setting switches in accordance with model table (see below).
3. Insert new key into ignition lock and turn on ignition.
4. Plug the programming device into diagnostic connector of the vehicle.
5. Within three seconds the device will beep three times and LED on it will light up with green.
6. Turn off the ignition and turn on. The new key is registered within system now, and engine could be started.

Attention! The installation of the switches is done carefully, only movements forward and backward. Do not apply pressure on top and do not push inward the switches in order to avoid their failure.

Switches setting table

Model	MY	Switches position
Lancer X	2006-2014	1, 2 – ON, the remaining ones – OFF
Lancer X Sportback	2008-2014	1, 4 – ON, the remaining ones – OFF
Lancer EVO X	2007-2014	1, 9 – ON, the remaining ones – OFF (NO TEST)
Lancer 9 (7315)	2003-2006	2 – ON, the remaining ones – OFF
Outlander (7129)	2003-2006	3 – ON, the remaining ones – OFF
Outlander XL	2006-2014	1, 3 – ON, the remaining ones – OFF
ASX	2010-2014	1, 10 – ON, the remaining ones – OFF
Grandis (4135)		8 – ON, the remaining ones – OFF
L200 (diesel), Pajero Sport II (diesel)	2006-2014	1, 5 – ON, the remaining ones – OFF
Pajero Sport II (diesel)	2008-2014	1, 7 – ON or 1, 5 – ON, the remaining ones – OFF
L200 (diesel), Pajero Sport II (diesel)	2011-2014	1, 9, 10 – ON, the remaining ones – OFF
Pajero IV (diesel)	2006-2014	1, 6 – ON, the remaining ones – OFF
Pajero IV (petrol) (1803)	2006-2010	7 – ON, the remaining ones – OFF
Pajero Pinin (9154)		6 – ON, the remaining ones – OFF
Pajero Sport II	2008-2011	1, 7 – ON, the remaining ones – OFF
Pajero Sport III, Montero Sport III (3828)		4 – ON, the remaining ones – OFF
Pajero III, Montero (5176)		5 – ON, the remaining ones – OFF
Peugeot 4007	2007-2014	1, 8 – ON, the remaining ones – OFF
Citroen C-croser	2007-2014	1, 8 – ON, the remaining ones – OFF (NO TEST)

The programming device has self-diagnostics mode. To activate this mode set all switches into ON position and give power according to OBD-II pinout (4, 5 – GND, 16 – +12V). If everything is OK, LED on the device will blink green and red alternately. If something is wrong the device will beep six times consecutive.

TO PURCHASE THE EQUIPMENT, AS WELL AS CONSULTING, MAINTENANCE,
PLEASE CONTACT US:

Url: <http://www.autodevice.net>

Email: info@autodevice.net